


## Features

- IP68 Standards
- Stainless Steel 316 Housing
- Meets FDA Compliancy
- Designed to operate in food applications
- Large LED Diffuse Ring Light
- M12 Quick Disconnect
- Driver built in – No External wiring to a driver
- Continuous operation or Strobe mode
- PNP and NPN Strobe input



Electrical Input	Voltage - 24 VDC +/- 5%    Maximum 75 Watts
Analog Intensity	The output is adjustable from 10-100% of brightness by a 0 -10 VDC signal
Continuous Mode	Light will be in continuous mode by leaving signal on strobe input
Strobe	PNP ▶ +5VDC or greater to activate.    NPN ▶ GND (<1VDC) to activate
Strobe Mode	The Light will operate in either continuous or strobe mode. In strobe mode, the output pulse width will track the pulse width of the strobe pulse.



1 = 24VDC  
 2 = NPN STROBE  
 3 = GND  
 4 = PNP STROBE  
 5 = 0-10VDC Analog

Standard M12 mating cable color code:

BROWN  
 WHITE  
 BLUE  
 BLACK  
 \*GRAY (GREEN/YELLOW)

\* 5 pin Standard M12 mating cable must be used: +VDC must be connected to pin 5 if Analog 0-10 VDC is not used.

## DLPW-NC-300x300 – XXX –» Part Number Key

**Product Family:**  
 Diffuse Ring Light  
 Wash Down  
 DLP 300mm x 300mm

**Color:**  
 625 – Red  
 White – WHI  
 470 – Blue  
 530 – Green  
 IR 850nm