


## Features

- IP68 Standards
- Stainless Steel 316 Housing
- Meets FDA Compliancy
- Designed to operate in food applications
- Driver built in – No External wiring to a driver
- PNP and NPN Strobe input



Electrical Input	Voltage - 24 VDC +/- 5% Maximum 75 Watts	
Continuous Mode	Light will be in continuous mode by leaving signal on strobe input	
Strobe	PNP ► +5VDC or greater to activate.	NPN ► GND (<1VDC) to activate
Strobe Mode	The Light will operate in either continuous or strobe mode. In strobe mode, the output pulse width will track the pulse width of the strobe pulse.	
<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;">  <p>1 = 24VDC 2 = NPN STROBE 3 = GND 4 = PNP STROBE 5 = No Connection</p> </div> <div style="width: 50%;"> <p>Standard M12 mating cable color code:</p> <p>BROWN WHITE BLUE BLACK *GRAY (GREEN/YELLOW)</p> </div> </div>		



## Important

Please note the light will turn on for 5 seconds at power up. This is required to initialize the settings in the light. Light will not be ready for use till the 5 second power up is completed.

## HOBLW – 300 x 150 – XXX —» Part Number Key

Product Family:  
Back Light  
SOBLW

Color:  
625 – Red  
White – WHI  
470 – Blue  
530 – Green  
IR 850nm